

Horizontal Metal Band Sawing Machine Series

卧式金属带锯床



G4230
卧式金属带锯床




G4038
卧式金属带锯床



G4028
卧式金属带锯床



- 液压进刀，夹紧，三级调速。
- 带锯条采用滚动轴承和硬质合金导向，使切割更精准。
- 小料成束锯切装置（可选）。
- 电动送料架（可选）
- Hydraulic feed, clamping, three speed.
- Band saw blade by rolling and hard alloy guide to make more precise cutting.
- Small material bunched sawing device (optional).
- Electric Feeding rack (optional)



产品型号	G4230	G4028	G4038
锯切能力 (mm) Cutting capacity	● Φ280 ■ 280x350	● Φ280 ■ 190x400	● Φ380 ■ 260x400
线速 (m/min) Wire-speed	27.45.70	27.45.70	28.50.78
带锯条规格 (mm) specification	3505x27x0.9	3505x27x0.9	4115x34x1.1
清洁 clean	钢丝刷和锯切液 Wire brush and cutting fluid	钢丝刷和锯切液 Wire brush and cutting fluid	钢丝刷和锯切液 Wire brush and cutting fluid
主电机 (kw) The main motor	2.2	2.2	3.0
液压 (kw) Hydraulic pressure	0.37	0.37	0.55
冷却泵 (w) Cooling pump	40	40	40
虎钳夹紧方式 Vise clamping	液压夹紧 Hydraulic clamping	液压夹紧 Hydraulic clamping	液压夹紧 Hydraulic clamping
锯条张紧方式 Saw blade tensioning	手动 Manually	手动 Manually	手动 Manually
机器重量 (kg) Weight	820	670	820
包装尺寸 (mm) Machine size (LxWxH)	2000x1150x1230	1800x1080x1300	2090x1080x1390

Double-Column Horizontal Metal Band Sawing Machine Series

双柱卧式金属带锯床



G4235/500

钢筋专用锯床

- 双立柱结构
- 液压虎钳
- 液压控制锯切进给
- 导向头结构合理，延长锯条的使用寿命
- 钢筋专用夹钳
- 上夹紧配套，液压捆紧钢筋功能

- Double-column structure
- Hydraulic Vise
- Hydraulic control cutting feed
- Reasonable guide head structure, to extend the service life of the saw blade
- Special clamp for reinforcement
- Upper clamping support, hydraulic binding function



Angle Horizontal Metal Band Sawing Machine Series

卧式转角度金属带锯床

- 机床除垂直锯切功能外，工作台可手动旋转0~45°角度，实现切料的斜切。
- 液压无级调速进给和液压自动抬升锯架。
- 液压加紧和松开工作，操作方便。
- 采用滚动轴承和硬质合金的锯条导向装置。



G4028 (45°~60°转角)

卧式转角度金属带锯床

- In addition to vertical sawing machine function, the table can be rotated manually 0 ~ 45° angle, cut the material to achieve the miter.
- Hydraulic variable speed hydraulic automatic feed and lifting the saw frame.
- Hydraulic intensify and release work, easy to operate.
- Rolling bearing and carbide saw blade guide.

产品型号

锯切能力 (mm) Cutting capacity

线速 (m/min) Wire-speed

带锯条 规格 (mm) specification

清洁 clean

主电机 (kw) The main motor

液压 (kw) Hydraulic pressure

冷却泵 (w) Cooling pump

虎钳夹紧方式 Vise clamping

锯条张紧方式 Saw blade tensioning

机器重量 (kg) Weight

包装尺寸 (mm) Machine size(LxWxH)

G4235/500

● Φ350

■ 400

27.45.70

4235x34x1.1

钢丝刷和锯切液

Wire brush and cutting fluid

3.0

0.55

40

液压夹紧

Hydraulic clamping

手动

Manually

960

2200x1260x1480

G-4028 (45°~60°转角)

● Φ280

■ 140

27.45.70

3900x34x1.1

钢丝刷和锯切液

Wire brush and cutting fluid

3.0

0.55

40

液压夹紧

Hydraulic clamping

手动

Manually

920

2080x1350x1360