

Double-Column Horizontal Metal Band Sawing Machine Series

双柱卧式金属带锯床

G4235

双卧式金属带锯床



G4240

双卧式金属带锯床

G4230

双卧式金属带锯床

- 双立柱结构
- 液压虎钳
- 液压控制锯切进给
- 导向头结构合理，延长锯条的使用寿命

- Double-column structure
- Hydraulic vise
- Hydraulic control cutting feed
- Reasonable guide head structure, to extend the service life of the saw blade



产品型号

锯切能力 (mm)	Cutting capacity
线速 (m/min)	Wire-speed
带锯条 规格 (mm)	specification
清洁	clean
主电机 (kw)	The main motor
液压 (kw)	Hydraulic pressure
冷却泵 (w)	Cooling pump
虎钳夹紧方式	Vise clamping
锯条张紧方式	Saw blade tensioning
机器重量 (kg)	Weight
包装尺寸 (mm)	Machine size (LxWxH)

G4230

● φ300
■ 300x500
27.45.70
3960x34x1.1
钢丝刷和锯切液
Wire brush and cutting fluid
3.0
0.55
40
液压夹紧
Hydraulic clamping
手动
Manually
900
2000x1260x1480

G4235

● φ350
■ 350x500
35.45.60.78
4115x34x1.1
钢丝刷和锯切液
Wire brush and cutting fluid
3.0
0.55
40
液压夹紧
Hydraulic clamping
手动
Manually
900
2000x1260x1480

G4240

● φ400
■ 400x500
27.45.60.78
4700x34x1.1
钢丝刷和锯切液
Wire brush and cutting fluid
4.0
1.1
90
液压夹紧
Hydraulic clamping
手动
Manually
1200
2400x1110x1600

Double-Column Horizontal Metal Band Sawing Machine Series

双柱卧式金属带锯床



G4250
双卧式金属带锯床

横切卧式金属带锯床
(定制)

Horizontal Metal Band Sawing Machine
(custom)




G4230
横切卧式金属带锯床(定制)



- 双立柱结构
- 液压虎钳
- 液压控制锯切进给
- 导向头结构合理，延长锯条的使用寿命

- Double-column structure
- Hydraulic Vise
- Hydraulic control cutting feed
- Reasonable guide head structure, to extend the service life of the saw blade

产品型号	G4250/70	G4250/70 (锯中)	G4230
锯切能力 (mm) Cutting capacity	<ul style="list-style-type: none"> ● Φ 500 ■ 500x700 	<ul style="list-style-type: none"> ● Φ 500 ■ 500x700 	<ul style="list-style-type: none"> ● Φ 200 ■ 200x900
线速 (m/min) Wire-speed	22.45.65	22.45.65	27.45.70
带锯条规格 (mm) specification	5640x41x1.3	5640x41x1.3	4860x34x1.1
清洁 clean	钢丝刷和锯切液 Wire brush and cutting fluid	钢丝刷和锯切液 Wire brush and cutting fluid	钢丝刷和锯切液 Wire brush and cutting fluid
主电机 (kw) The main motor	4.0	4.0	3.0
液压 (kw) Hydraulic pressure	1.5	1.5	1.1
冷却泵 (w) Cooling pump	90	90	40
虎钳夹紧方式 Hydraulic clamping	液压夹紧 Hydraulic clamping	液压夹紧 Hydraulic clamping	液压夹紧 Hydraulic clamping
锯条张紧方式 Saw blade tensioning	手动 Manually	手动 Manually	手动 Manually
机器重量 (kg) Weight	1600	1600	1500
包装尺寸 (mm) Machine size (LxWxH)	2800x1200x1880	2800x1200x1880	2600x1400x1500



Double-Column Horizontal Metal Band Sawing Machine Series

双柱卧式金属带锯床



HL-7040

双卧式金属带锯床(模具材料专切)




G4240/70

双卧式金属带锯床锯中下料 (双圆柱系列模具材料专切)

- 双立柱结构
- 液压虎钳
- 液压控制锯切进给
- 导向头结构合理, 延长锯条的使用寿命

- Double-column structure
- Hydraulic vise
- Hydraulic control cutting feed
- Reasonable guide head structure, to extend the service life of the saw blade



产品型号	HL-7040 (锯中)	G4240/70 锯中(双圆柱)
锯切能力 (mm) Cutting capacity	● φ400 ■ 400x700	● φ400 ■ 400x700
线速 (m/min) Wire-speed	18.30 45.52	18.30 45.52
带锯条 规格 (mm) specification	5100x41x1.3	5560x41x1.3
清洁 clean	钢丝刷和切削液 Wire brush and cutting fluid	钢丝刷和切削液 Wire brush and cutting fluid
主电机 (kw) The main motor	4.0(6P)	4.0(6P)
电机功率 液压 (kw) Hydraulic pressure	1.1	1.1
冷却泵 (w) Cooling pump	90	90
虎钳夹紧方式 Vise clamping	液压夹紧 Hydraulic clamping	液压夹紧 Hydraulic clamping
锯条张紧方式 Saw blade tensioning	手动 Manually	手动 Manually
机器重量 (kg) Weight	1500	1500
包装尺寸 (mm) Machine size(LxWxH)	2500x1250x1700	2800x1200x1700

- 双立柱结构
- 液压虎钳
- 液压控制锯切进给
- 导向头结构合理, 延长锯条的使用寿命
- 根据要求可定做液压张紧锯条
- 锯条省、刚性好、力量大

- Double-column structure
- Hydraulic vise
- Hydraulic control cutting feed
- Reasonable guide head structure, to extend the service life of the saw blade
- Can be customized according to the requirements of hydraulic blade tensioning
- Saw province, rigidity and strength